This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

51) International Patent Classification ⁶ : A61K 9/12	A1	(11) International Publication Number: WO 97/40819 (43) International Publication Date: 6 November 1997 (06.11.97)
21) International Application Number: PCT/US 22) International Filing Date: 21 April 1997 (20) 23) Priority Data: 60/016,428 29 April 1996 (29,04.96) 24) Applicant: DURA PHARMACEUTICALS, INC. 5880 Pacific Center Boulevard, San Diego, CA 921 25) Inventors: SCHULTZ, Robert, 5880 Pacific Center Boulevard, San Diego, CA 92121 (US). WITHAM, Clyde; 588 26) Center Boulevard, San Diego, CA 92121 (US). Malcolm; 5880 Pacific Center Boulevard, San Diego, CA 92121 (US). 27) Agents: OHRINER, Kenneth, H. et al.; Lyon & Lyon Suite 4700, 633 West Fifth Street, Los Angeles, CA 2066 (US).	US/US 21 (US/US 21 (US oulevar 0 Pacif HILI ego, C	(81) Designated States: AU, BG, BR, CA, CN, CZ, FI, HU, IL, JP, KP, KR, MN, MX, NO, NZ, PL, RO, SG, SK, TR, UA, VN, Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(57) Abstract

A method for inhalation of a dry powder drug includes the steps of providing a dry powder drug composition having a drug particle size of from about 1-7 microns and a mass median aerodynamic diameter of the delivered aerosol of from about 3.5 to 5.5 microns. This composition is loaded into an inhaler which is generally flow rate independent, and with the inhaler having an inspiration flow resistance of about 1.2 to .21 (cmHzO)^{1/2} over the range of about 1.5-60 L/min. The patient inhales the drug composition from the inhaler with an inspiration flow rate of about 15-60 L/min, resulting in a delivery efficiency measured by respirable fraction greater than 20 %.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		=c	Sania	LS	Lesotho	SI	Slovenia
AL	Albania	ES	Spain	LT	Lithuania	SK	Slovakia
AM	Armenia	Fi	Finland			SN	Senegal
AT	Austria	FR	France	LU	Luxembourg		
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	1E	ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	laraci	MR	Mauritania	UG	Uganda
BY	Belarus	15	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ.	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenys	NL	Netherlands	YU	Yugoslavia
CII	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
СМ	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korca	PT	Portugal		
Ċυ	Cuba	KZ	Kazakstan	RO	Romania		
cz	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	u	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 97/40819

PCT/US97/06621

1

DESCRIPTION

Methods of Dry Powder Inhalation

State-of-the-Art

10

15

20

25

Considerable information regarding the in-vitro and in viv-performance of metered dose inhalers and dry powder inhalers has been reported in literature. In general, metered dose inhalers are inhalation flow independent, but require significant coordination and even then will deliver only about 20% of the nominal does to the lungs. Radiolabelled deposition studies of metered dose inhalers typically demonstrate the usual 3 micron particles deposit mainly in the more central airways. Recently, 3M Corporation, Minneapolis, MN, USA, has presented data that indicates that if the particle size could be reduced to a mass median aerodynamic diameter (MMAD) of 1.5 microns an increase in the total amount of particles and peripheral deposition could result. result appears to confirm the more uniform belief that smaller particles are required to maximize peripheral deposition (i.e. particles in the 1-2 microns size range).

Now in the case of dry powder inhalers, most studies have shown the major issue surrounding dry powder delivery is related to the flow rate dependence. The performance of the dry powder inhalers now in use vary significantly with inhalation flow rates ranging from 15 to 120 liters/min inspiratory effort. In general, at least 60 liters/min inspiratory flow has been required to consistently deaggregate a dry powder sufficiently to result in particles which could be inhaled. For some

products, inhalation flow rates significantly greater than 60 L/min are required before sufficient deaggregation can occur. Both the total amount of drug formulation delivered to the patient as well as the aerodynamic particle size are affected by increasing the inhalation flow rate. For example, at 30 L/min, aerodynamic sizes of the active particles may be as large as 8 to 10 microns but above 60 L/min the same metered dose inhaler formulation may be 2-4 microns. In addition, the dose-to-dose variation may be significantly greater as the flow rate is decreased.

Unfortunately, requiring the patient to breathe forcefully when using a metered dose inhaler is in direct opposition to maximizing deposition. Traditional thinking is that 30 L/min is a well controlled inhalation flow rate. And, currently no data has been presented which shows that using existing metered dose inhaler technology, significant uniform and peripheral particle deposition had occurred, at any flow rate.

Finally, it is now generally believed that for a protein to be efficiently delivered systemically through the lungs, a very small particle size is required to facilitate peripheral deposition, preferably in the alveoli. The size often considered necessary for this purpose is in the range of one micron.

Statement of the Invention

5

10

15

20

25

Utilizing the dry powder inhalation system described in PCT/US93/09751, published 28 April 1994, and incorporated by reference (referred to here as the SPIROS

3

system), the following in vitro and in vivo observations have been made:

1. The in vitro delivery of several drug/lactose blends has been shown to be flow rate independent over a range flow rates from 15 to 60 L/min. Both the size of the active particles and the amount of drug delivered were independent of flow rate.

5

10

15

20

- 2. Utilizing a radiolabelled technique, the flow rate independence of the delivery system was confirmed in vivo (15 to 60 L/min). In addition, this study clearly indicated that even with a slow inhalation rate (less than 60 L/min), the drug was delivered uniformly throughout the lung, including the periphery. In fact, there is a tendency to have higher peripheral lung deposition at the low flow rate.
- 3. In the metered does inhaler studies, where the in vitro determined MMAD is between 2 to 3 microns, in vivo deposition is typically quoted as between 10 to 20% of the nominal dose. Deposition of albuterol from the Spiros system was shown to be equal to or better than what is expected from metered dose inhalers, even though the aerodynamic particle size of the active particle was approximately 4.5 microns.
- 4. Recent pharmacokinetic (blood level) data from a comparison of beclomethasone delivered from a metered dose inhaler compared to Spiros, indicated that twice as much drug was delivered to the lung from the Spiros system. Again, the particle size of the active particle in the dry powder inhaler system was between 4 to 5 microns, while the metered dose inhaler formulation was between 3 to 4 microns.

4

5. Using calcitonin as a model peptide for systemic delivery, the bioactivity following dosing with the Spiros system has been estimated to be greater than 20% compared to a subcutaneous injection. In contrast, an approved nasal product has only 3% bioavailability. Surprisingly, the particle size of the calcitonin from the calcitonin/lactose blend was 4-5 microns, yet excellent systemic availability was achieved (>20%).

5

10

15

20

25

30

Using the above observations, the following conclusions regarding dry powder delivery can now be made.

Until a dry powder inhaler was developed which adequately deaggregated the powder at low inspiratory flow rates, it was not possible to separate out the performance of the dry powder inhaler from the patient inhalation maneuver. Thus, the relationship between particle size and deposition was confused with the performance of the dry powder inhaler itself. With the development of the Spiros system, we have now demonstrated that under low flow rate conditions, particle sizes which would be considered on the upper end of achieving good lung deposition can actually provide deposition uniformly throughout the respiratory tract.

Importantly, the delivery of the dry powder from the Spiros system is no longer degraded by the patient's inhalation flow rate, as is the case with existing dry powder inhalers. Slow deep inspiration is key to the increased drug delivery and peripheral deposition. Thus, the delivery system must efficiently operate under these conditions. With the deagglomerating dry powder at low inhalation flow, surprising good results were obtained

5

over what could be expected for commercially available metered dose inhalers or dry powder inhalers.

The results which were obtained in vivo were possible because 1) Spiros is inhalation flow rate independent, and 2) Spiros efficiently deaggregates the powder. Therefore, patients were able to be trained and benefit from the slow deep inhalation maneuver. The slow deep inhalation permits more of the particles to navigate past the throat (and not be collected by impaction) and be available to deposit in the lung. Secondly, the slow deep inhalation maneuver fully dilates the lungs, driving the particles further into the lung, and inhibits premature impaction of the larger particles in the upper airways.

5

10

15

20

25

To facilitate the slow inhalation, some device resistance is required. If no resistance is encountered, then it is difficult for a patient to inhale slowly. This is what is often observed for metered dose inhalers and some dry powder inhalers such as Rotohaler and Spinhaler. If flow resistance is too high, patient discomfort results when the inhaler is used at the optional flow rate. can also result in higher air velocity in passageways. This increase in velocity increases upper deposition by impaction. Less deposited drug is then available to the lower regions of the lung. The drug may be a systemic or topical drug for treating asthma. drug may be a protein, a polypeptide or a hormone, for treating lung or other conditions.

5

10

15

20

Detailed Description

- 1. A dry powder inhalation system consisting of micronized drug in the 1 to 7 micron range, alone or in blends of lactose or some other suitable inert carrier (i.e., sugars, salts).
- 2. The inhalation system should be flow rate independent over the range of interest, i.e., 10 or 15 -60 L/min.
- 3. The mass median aerodynamic diameter (MMAD) of the delivered aerosol (Cascade impactor 26.3 L/min, UPS throat) should be 3.5 7 and preferably 3 6 microns. Additionally, the respirable fraction (fraction of particles penetrating the impactor inlet with a particle size less than 5.8 microns) should be greater than 20%. The most preferred level would be greater than 30 to 40%. This describes the efficiency of the device to deagglomerate the powder. A device such as the Beclomethasone Rotohaler which could be considered flow rate independent over this range delivers an aerosol of 10 microns and a respirable fraction of 2.6%.

The device resistance (slope of the flow vs. pressure drop curve (in units of (cm $\rm H_2O^{1/2}$)) should be .12 to .21 with a most preferred range of 0.12 to 0.18.

7

Claims:

5

10

 A method for inhalation of a dry powder drug, comprising the steps of:

- a) providing a dry powder drug composition having a drug particle size of from about 1-7 microns and mass median aerodynamic diameter of the delivered aerosol of from about 3 to 6 microns;
- b) loading the dry powder drug composition into an inhaler which is generally flow rate independent, and with the inhaler having an inspiration flow resistance of about .12 to .21 (cm H₂O)^N) over the range of about 10-60 L/min;
- c) inhaling the drug composition from the inhaler with an inspiration flow rate of about 15-60 L/min, resulting in a delivery efficiency measured by respirable fraction of at least 20%.
- 20 2. The method of claim 1 wherein the drug composition includes active particles and the aerodynamic particle size of the active particles is about 4.5 microns.
- The method of claim 1 wherein the drug comprises
 a systemic or a topical drug for treating asthma.
 - 4. The method of claim 1 wherein the drug comprises a protein, a polypeptide, or a hormone.

- 5. The method of claim 1 wherein the percent of particles greater than 5 microns is about 30-90.
- 6. The method of claim 1 wherein the inhaler has a flow resistance of from about .12 to .18 (cm $H_2O)^{\,\text{M}}$.
- 5 7. The method of claim 1 wherein the drug composition includes an inert carrier.
 - 8. The method of claim 1 wherein the drug comprises beclamethasone.
- 9. The method of claim 1 wherein the respirable fraction (fraction of particles penetrating the inpactor inlet with a particle size less than about 5.8 microns) is at least 20%.
- 10. The method of claim 1 wherein the flow resistance is about .12 to .21 $(cmH_2O)^*$ over the range of 15 15-60 L/min.
 - 11. The method of claim 1 wherein the mass median aerodynamic diameter of the delivered aerosol is from about 3.5 to 5.5 microns.

INTERNATIONAL SEARCH REPORT

International application No. PCT/US97/06621

	SSIFICATION OF SUBJECT MATTER :A61K 9/12						
US CL :424/45; 128/203.12							
	to International Patent Classification (IPC) or to bot	n national classification and IPC					
	LDS SEARCHED ocumentation searched (classification system follow	ed by classification symbols)					
	424/45; 128/203.12	or of classification symbols					
Documenta	tion searched other than minimum documentation to the	ne extent that such documents are included	in the fields searched				
Electronic o	lata base consulted during the international search (r	ame of data base and, where practicable	, scarch terms used)				
C. DOC	UMENTS CONSIDERED TO BE RELEVANT						
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.				
Y	US 4,681,752 A (MELILLO) 2 document.	1 July 1987, see entire	1-11				
Y	US 4,810,488 A (JINKS) 07 March 1989, see entire 1-11 document.						
Υ, Ρ	US 5,524,613 A (HABER et al.) 11 June 1996, see entire document.						
		*					
ĺ							
Further documents are listed in the continuation of Box C. See patent family annex.							
* Special categories of cited documents: The document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the investion.							
*E' carlier document published on or after the international filing date "X" document of particular relavance; the claimed invention cannot							
cita	nument which may throw doubts on priority claims(s) or which is it to establish the publication date of another citation or other cital reason (as specified)	"Y" document of particular relevance; the	claimed invention cannot be				
P doc	ument published prior to the international filling date but later than	combined with one or more other such being obvious to a person skilled in th "&" document member of the same patent	s documents, such combination & art				
108	priority date claimed	Date of mailing of the international sea					
20 JUNE		Q 9 JUL 19					
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231		Authorized officer Raj Bawa, Ph.D.					
Washington Facsimile No		Telephone No. (703) 308-2351					
	A/210 (second sheet)(July 1992)#						